

Philips
PAL coax cable

7,5 m

> 75 dB White

SWV2919W



Ensure a reliable connection

with this PAL coax cable

Depend on this cable to provide you with a reliable audio/video connection between components.

Enjoy good picture quality

- Nickel-plated connectors for reliable contact

Enjoy good audio quality

- High purity copper conductor for reliable signal transfer

Protects against signal loss

- Bare copper shielding

Easy installation

- Non-slip ergonomic grip for easy use

Enjoy extended durability

- Molded plug for secure connections
- Flexible PVC jacket
- Rubber strain relief

PHILIPS

sense and simplicity

PAL coax cable
7,5 m > 75 dB White

Specifications

Packaging dimensions

- **Packaging dimensions (W x H x D):**
15.0 x 23.1 x 3.6 cm
- **Nett weight:** 0.370 kg
- **Gross weight:** 0.382 kg
- **Tare weight:** 0.012 kg
- **EAN:** 87 12581 37953 7
- **Number of products included:** 1
- **Packaging type:** Card

Outer Carton

- **Outer carton (L x W x H):** 57.2 x 26.7 x 17.8 cm
- **Nett weight:** 4.440 kg

- **Gross weight:** 5.280 kg
- **Tare weight:** 0.840 kg
- **EAN:** 87 12581 37955 1
- **Number of consumer packagings:** 12

Inner Carton

- **Inner carton (L x W x H):** 24.9 x 17.8 x 15.2 cm
- **Nett weight:** 1.480 kg
- **Gross weight:** 1.630 kg
- **Tare weight:** 0.150 kg
- **EAN:** 87 12581 37954 4
- **Number of consumer packagings:** 4

SWV2919W/10

Product highlights

Bare copper shielding

Bare copper shielding protects against signal loss.

Easy grip

This non-slip grip makes connecting your components easy and ergonomically comfortable.

Flexible PVC Jacket

Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

High purity copper

This copper conductor provides high accuracy in signal transfer with minimal resistance.

Molded plug

Molded plugs ensure secure connections between components and offer extended durability.

Nickel-plated connectors

Nickel-plated connectors establish a clean contact between the cable and connector for a reliable connection.

Rubber strain relief

Rubber strain relief provides a secure, yet flexible juncture between the cable and the plug.



Issue date 2008-10-28

Version: 1.1.7

12 NC: 8670 000 35433
EAN: 87 12581 37953 7

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips
Electronics N.V. or their respective owners.

www.philips.com